



Product Features:

- High precision gap connection by CNC technology, gap tolerance within 0.01mm
- IP65 Waterproof, suitable for all weather conditions use.
- Easy maintenance .
- Light weight cabinet, easy for installation and transportation.
- Energy saving solution available for special request.

Model	IFPRO-330	IFPRO-400	IFPRO-500	IFPRO-660	IFPRO-800	IFPRO-100	
Module Parameter	Pixel Pitch	P3.33mm	P4mm	P5mm	P6.67mm	P8mm	P10mm
	Application	Outdoor					
	Pixel Configuration	SMD1921			SMD3535		
	Pixel Density (dots/m ²)	90000	62500	40000	22477	15625	10000
	Resolution (W×H)	96*48	80*40	64*32	48*24	32*16	32*16
Cabinet Parameter	Dimension (mm)	320*160					
	Module qty (W×H)	3*6					
	Resolution (W×H)	288*288	244*244	192*192	144*144	128*96	96*96
	Size (m ²)	0.9216					
	Dimension (mm)	960*960					
	Weight (kg)	27KG/pcs					
	Material	Magnesium outdoor cabinet/Die-casting Aluminum outdoor Cabinet					
Screen Parameter	Power Supply	5V60A					
	Curve Design	Available					
	Brightness (nits)	5500-6000	5500-6000	5500-6000	6500-7000	6000-6500	6000-6500
	Color Temperature (K)	3200—9300 adjustable					
	Viewing Angle (H/V°)	H: ±140°/V: ±120°					
	Contrast	3000:1					
	Max. Power Consumption	780	780	683	780	731	780
	Ave. Power Consumption	351	351	307	351	329	351
	Input Voltage (V)	AC200~240V, 47-63 (Hz)					
	Frame Frequency (Hz)	60					
	Driving Mode	1/12	1/10	1/8	1/6	1/5	1/2
	Gray Scale	16384/≥14bits					
	Refresh Rate (Hz)	≥1920					
	IP Grade	IP65					
	Optimal Viewing Distance(m)	≥3m	≥4m	≥5m	≥6.67m	≥8m	≥10m
Working Temperature / Storage Temperature /	-30 - 60 / 10%-90%RH -40 - 70 / 10%-95%RH						
Certification	CCC, CE, ROHS						
Lifespan	100,000H						
Signal Interface	DVI						
Source Compatibility	YPbPr, PAL/NTSC, S-Video, HDMI, VGA, HD_SDI						
Maintenance type	Back						

